

## AGRIMAX RT 765 - Technical Specifications



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	280/70 R 16
LI/SS	112 A8/B

## Dimensions US Standard

Usa code	94021895
Section Width (inch)	11.1
Overall Diameter (inch)	31.4
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	93.3
Rim Rec	W 9
Rim Alt	W 8 ; W 8 L ; W 10
ECE	E4-106R-000633
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1170	1330	1530	1730	1930	2130	2300	2470
25	1170	1330	1530	1730	1930	2130	2300	2470
20	1250	1430	1640	1850	2070	2280	2470	2650
5 LT	1570	1800	2060	2330	2590	2850	3090	3320
5 HT	1250	1430	1640	1850	2070	2280	2470	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/02/2025 05:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..