

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	320/70 R 20
LI/SS	123 A8/B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	982
Static Loaded Radius (mm)	445
Rolling Circumference (mm)	2938
SRI (mm)	475
Rim Rec	W 10
Rim Alt	W 9; W 11
ECE	E4-106R-000644
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	730	840	965	1085	1210	1335	1445	1550
40	730	840	965	1085	1210	1335	1445	1550
30	785	900	1030	1165	1295	1430	1545	1660
10 LT	980	1125	1290	1460	1625	1790	1935	2080
10 HT	785	900	1030	1165	1295	1430	1545	1660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/02/2025 05:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..