

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/70 R 28
LI/SS	133 D

Dimensions US Standard

Usa code	94062171
Section Width (inch)	16.5
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.8
Rolling Circumference (inch)	158.3
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-005520
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	2500	2910	3320	3730	4130	4540
30	2630	3060	3490	3920	4350	4770
25	2740	3200	3640	4090	4540	4980
20	2880	3350	3820	4290	4760	5220
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2880	3350	3820	4290	4760	5220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 10:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..