

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	600/70 R 30
LI/SS	152 D

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1602
Static Loaded Radius (mm)	711
Rolling Circumference (mm)	4774
SRI (mm)	750
Rim Rec	DW 20 B
Rim Alt	DW 18 L ; W 18 L
ECE	E11-106R-005523
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1955	2275	2595	2915	3235	3550
50	2055	2390	2725	3060	3395	3730
40	2140	2490	2840	3190	3540	3890
30	2250	2615	2985	3350	3720	4085
10 LT	2620	3050	3475	3905	4335	4760
10 HT	2250	2615	2985	3350	3720	4085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..