

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/85 R 24 (9.5 R 24)
LI/SS	109 A8/B

Dimensions International Standard

Section Width (mm)	251
Overall Diameter (mm)	1036
Static Loaded Radius (mm)	475
Rolling Circumference (mm)	3104
SRI (mm)	500
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E4-106R-000638
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	570	660	755	845	940	1030
40	570	660	755	845	940	1030
30	610	710	810	910	1010	1105
10 LT	765	890	1015	1140	1265	1385
10 HT	610	710	810	910	1010	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/02/2025 10:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..