

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/85 R 36 (12.4 R 36)
LI/SS	128 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1458
Static Loaded Radius (mm)	672
Rolling Circumference (mm)	4404
SRI (mm)	700
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000762
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	990	1155	1315	1480	1640	1800
40	990	1155	1315	1480	1640	1800
30	1065	1240	1410	1585	1760	1930
10 LT	1330	1550	1765	1985	2200	2415
10 HT	1065	1240	1410	1585	1760	1930

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..