

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 38 (12.4 R 38)
LI/SS	143 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1509
Static Loaded Radius (mm)	700
Rolling Circumference (mm)	4580
SRI (mm)	725
Rim Rec	W 11
Rim Alt	W 9 ; W 10 ; DW 10
ECE	E4-106R-000781
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	985	1145	1500	1830	1990	2130	2320	2510	2725
40	985	1145	1500	1830	1990	2130	2320	2510	2725
30	1055	1230	1610	1960	2135	2280	2485	2690	2920
10 LT	1320	1540	2015	2450	2670	2855	3110	3365	3655
10 HT	1055	1230	1610	1960	2135	2280	2485	2690	2920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..