

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	380/85 R 30 (14.9 R 30)
LI/SS	135 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1408
Static Loaded Radius (mm)	633
Rolling Circumference (mm)	4190
SRI (mm)	675
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000594
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1200	1400	1595	1790	1985	2180
40	1200	1400	1595	1790	1985	2180
30	1285	1495	1705	1915	2125	2335
10 LT	1610	1875	2140	2400	2665	2925
10 HT	1285	1495	1705	1915	2125	2335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..