

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	380/85 R 38 (14.9 R 38)
LI/SS	139 A8/B

Dimensions US Standard

Usa code	94033119
Section Width (inch)	15
Overall Diameter (inch)	63.4
Static Loaded Radius (inch)	29
Rolling Circumference (inch)	190.6
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000660
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2950	3440	3910	4400	4880	5350
25	2950	3440	3910	4400	4880	5350
20	3160	3680	4200	4720	5240	5740
5 LT	3960	4610	5250	5900	6550	7190
5 HT	3160	3680	4200	4720	5240	5740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..