

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	460/85 R 30 (18.4 R 30)
LI/SS	145 A8/B

Dimensions US Standard

Usa code	94046775
Section Width (inch)	18.7
Overall Diameter (inch)	60.8
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	179.6
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E4-106R-000774
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3520	4100	4670	5250	5820	6390
25	3520	4100	4670	5250	5820	6390
20	3770	4390	5000	5620	6240	6840
5 LT	4720	5490	6260	7030	7800	8580
5 HT	3770	4290	5000	5620	6240	6840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..