

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/80 R 46 (18.4 R 46)
LI/SS	158 A8/B

Dimensions US Standard

Usa code	94021826
Section Width (inch)	18.9
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	35.2
Rolling Circumference (inch)	231.1
Rim Rec	DW 16 A ; W 16 A ; DD 16
Rim Alt	W 16 L ; DD 16 L ; DW 16 L
ECE	E4-106R-001731
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	4410	5060	5810	6560	7310	8060	8720	9350
25	4410	5060	5810	6560	7310	8060	8720	9350
20	4720	5420	6230	7020	7830	8630	9340	10030
5 LT	5910	6790	7790	8800	9800	10800	11680	12550
5 HT	4720	5420	6230	7020	7830	8630	9340	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..