

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 380/105 R 54
LI/SS	180 D

Dimensions US Standard

Usa code	94075843
Section Width (inch)	15.7
Overall Diameter (inch)	84.3
Static Loaded Radius (inch)	38.7
Rolling Circumference (inch)	256
Rim Rec	W 13 A
Rim Alt	W 12 ; DW 12 ; DW 13 ; DW 13 L
ECE	E11-106R-0010148
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	7710	8670	9470	9960	10430	10750	11070	11630	12200	12680	13170	13960	14120	14440	14760	15400	16040
from 40 to 25	8470	9530	10410	10940	11470	11820	12170	12790	13410	13940	14470	15350	15520	15880	16230	16940	17640
20	8650	9730	10620	11160	11700	12060	12430	13060	13680	14220	14760	15660	15840	16200	16560	17280	17990
12	8810	9910	10830	11380	11930	12300	12670	13310	13950	14500	15050	15970	16150	16520	16880	17620	18350
5	9320	10490	11460	12040	12610	13010	13400	14070	14750	15340	15920	16890	17080	17460	17860	18630	19400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/02/2025 10:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..