

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 420/95 R 50
LI/SS	177 D

Dimensions International Standard

Section Width (mm)	419
Overall Diameter (mm)	2068
Static Loaded Radius (mm)	943
Rolling Circumference (mm)	6210
SRI (mm)	975
Rim Rec	DW 14
Rim Alt	DW 13 ; W 13 ; W 14
ECE	E4-106R-002651
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
70	3715	4115	4515	4710	4980	5110	5245	5510	5775	5975	6240	6440	6640
From 65 to 40	4085	4525	4960	5180	5475	5620	5765	6055	6350	6570	6860	7080	7300
30	4165	4615	5060	5285	5580	5730	5880	6175	6475	6700	6995	7220	7445
20	4250	4705	5160	5385	5690	5840	5995	6295	6600	6830	7130	7360	7590
10	4495	4975	5460	5700	6020	6180	6340	6660	6985	7225	7545	7785	8030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/02/2025 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..