

# **AT 111 HD - Technical Specifications**



### Description

AT 111 HD is suitable for all-terrain sport racing with ATVs. The increased tread depth and the thick sidewall provide extra grip and braking control in addition to extraordinary traction and high-speed control in power slides. AT 111 HD ensures an extended tire life-cycle.

### UM

US Standard

# Construction

BIAS

Machinery Agriculture: ATV

| Version   | STANDARD        |
|-----------|-----------------|
| Туре      | TL              |
| Tyre Size | AT 20 X 11 - 10 |

## **Dimensions US Standard**

| Usa code                | 94027002       |
|-------------------------|----------------|
| Ply Rating              | 6              |
| Section Width (inch)    | 11             |
| Overall Diameter (inch) | 19.9           |
| Rim Rec                 | 9.0 AT         |
| Rim Alt                 | 8.5 AT         |
| ECE                     | E4-75R-0006327 |

## Load capacity (lbs)

| mph / psi | 7   |
|-----------|-----|
| 62        | 330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

### Printed on 17/02/2025 00:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..