

COMMANDER RADIAL - Data Sheet



Description

COMMANDER RADIAL has been specially designed for the domestic Indian market to meet the specific needs of local agriculture. The tire is perfect for tractors employed in soil tillage, haulage, and harvesting operations. The special dual-angle lug provides excellent traction and maximum self-cleaning properties making COMMANDER RADIAL suitable for transport operations in the fields and on the road. The sturdy polyester carcass improves load carrying capacity and enhances stability upgrading the overall tire performance in various soil conditions. Moreover, the cut-and-chip-resistant compound and the strong multi-layered belts (1500/2) provide improved puncture resistance. All these features along with the special tread design and its robust lug base ensure a longer tire life-cycle.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
400/85 R 28 (15.9 R 28)	STANDARD	134 D/137 A8	W13	W12	410	1380	624	4134	650	TL	E11-106R-0010180
440/85 R 28 (17.9 R 28)	STANDARD	140 D/143 A8	W15		460	1450	654	4333	675	TL	E11-106R-0010179

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 14:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..