

# COMMANDER (R) - Technical Specifications



## Description

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Harvester • Tractor

Version	STANDARD
Type	TT
Tyre Size	11.2 - 24
LI/SS	120 A8

## Dimensions US Standard

Usa code	94054367
Ply Rating	12
Section Width (inch)	11.6
Overall Diameter (inch)	44.3
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	137.1
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004616
TRA Code	R1

## Load capacity (lbs)

mph / psi	52
25	3085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 16:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..