

COMMANDER (R) - Data Sheet



Description

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Harvester • Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
9.5 - 20	STANDARD	R1	109 A6	12	W 8	W 7	245	970	456	2949	TT	1	E11-106R-005246
11.2 - 24	STANDARD	R1	123 A6	12	W 10	W 9	295	1125	533	3483	TT		E11-106R-004616
12.4 - 24	STANDARD	R1	128 A6	12	W 11	W 10	328	1180	569	3669	TT	1	E11-106R-004365
12.4 - 24	STANDARD	R1	121 A6	8	W 11	W 10	328	1180	569	3669	TT	1	E11-106R-005208
9.5 - 24	STANDARD	R1	114 A6	12	W8	W 7	245	1065	507	3308	TT	1	E11-106R-004364
12.4 - 28	STANDARD	R1	125 A6	12	W 11	W 9 ; W 10	320	1285	600	3946	TT	1	E11-106R-002999
13.6 - 28	STANDARD	R1	128 A6	12	W 12	W 11	360	1345	623	4068	TT	1	E11-106R-003002
14.9 - 28	STANDARD	R1	134 A6	12	W 13	W 11 , W 12	388	1380	642	4176	TT	1	E11-106R-005966
15.9 - 28	STANDARD	R1	140 A6	12	W 13	W 11 , W 12	405	1410	0	0	TT	0	E11-106R-009016
16.9 - 28	STANDARD	R1	143 A6	12	W 15 L	W 14 L	440	1435	663	4274	TT	1	E11-106R-003627
16.9 - 28 (21L)	STANDARD	R1	143 A6	12	W 15 L	W 14 L	440	1435	0	0	TT	0	E11-106R-009015
17.9 - 28	STANDARD	R1	144 A6	12	W 15 L	W 14 L	458	1515			TT	1	E11-106R-007701
16.9 - 30	STANDARD	R1	144 A6	12	W 15 L	W 14 L	440	1480	689	4537	TT		E11-106R-006618
18.4 - 30	STANDARD	R1	151 A6	14	W 16 L		472	1565	734	4834	TT	1	E11-106R-004525
18.4 - 30	STANDARD	R1	155 A6	18	W 16 L		472	1565	734	4834	TT	1	E11-106R-004368
18.4 - 30	STANDARD	R1	155 A6	18	W 16 L		472	1565	734	4834	TL	1	E11-106R-004368
18.4 - 30	STANDARD	R1	139 A6	8	W 16 L		472	1565	734	4834	TT	1	E11-106R-005247
9.5 - 36	STANDARD	R1	126 A6	12	W 8	W 7	246	1376	0	0	TT		E11-106R-007809

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 16:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..