

# EARTHMAX SR 44 - Technical Specifications



## Description

EARTHMAX SR 44 is an **All Steel** radial tire suitable for a variety of applications including mining, haulage and logging applications. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) is able to optimize productivity whatever your operation is.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: On/Off Truck

Version	STANDARD
Type	TT
Tyre Size	12.00 R 20

## Dimensions International Standard

Overall Width (mm)	305
Overall Diameter (mm)	1138
Static Loaded Radius (mm)	532
Rolling Circumference (mm)	3408
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4
Tread Depth	25

## Load capacity (Kg)

km/h / bar	7.75
50	4160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/02/2025 05:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..