

EARTHMAX SR 45 - Data Sheet



Description

EARTHMAX SR 45 is an **All Steel** radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 is the ideal tire for all operations requiring high traction.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
18.00 R 33	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5	--	505	1870	856	5608	TL	55	185
18.00 R 33	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		505	1870	856	5608	TL	55	185
18.00 R 33	HEAT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5	--	505	1870	856	5608	TL	55	256
18.00 R 33	STANDARD COMPOUND	E4	**	191 B	13.00/2.5	--	505	1870	856	5608	TL	55	220
18.00 R 33	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		505	1870	856	5608	TL	55	220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/02/2025 04:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..