

## FL 630 SUPER - Technical Specifications



### Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 R 22.5
LI/SS	162 D

## Dimensions US Standard

Usa code	94056149
Section Width (inch)	23.4
Overall Diameter (inch)	48.5
Static Loaded Radius (inch)	22
Rolling Circumference (inch)	147.9
Rim Rec	AG 20.00
ECE	E11-106R-004759

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3480	3910	4870	5530	6390	7250	7910	8690	9530
40	3820	4300	5350	6070	7020	7960	8700	9530	10470
30	4630	5200	6470	7350	8500	9630	10530	11540	12680
25	5200	5840	7260	8270	9550	10820	11830	12960	14240
15	6040	6790	8440	9600	11090	12580	13730	15060	16540
5	6890	7740	9620	10930	12630	14330	15650	17160	18850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..