

## FLOTATION V LINE - Technical Specifications



### Description

FLOTATION V LINE has been specially designed for trailers in transport applications. It shows high flotation capability and ensures low soil compaction protecting the field. FLOTATION V LINE allows you to carry high loads at low pressure maximizing your business productivity.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Trailer

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/ 156 B

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00

## Load capacity (Kg)

km/h / bar	1.50	1.80	2.10
10 FR	5175	5755	6300
20 FR	4655	5180	5670
30 FR	4140	4605	5040
40 FR	3695	4110	4500
50 FR	3325	3700	4000
10 DW	3620	4030	4410
20 DW	3255	3630	3970
30 DW	2895	3225	3530
40 DW	2585	2880	3150
50 DW	2325	2590	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 08:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..