

LG RIB PLUS - Technical Specifications



Description

LG RIB PLUS is a lawn and garden tire suitable for applications with mowers, small tractors and tedders. Its tread pattern has been specially designed for making the tire gentle on the ground preventing turf damages, while at the same time making the handling easier. The round profile makes LG RIB PLUS able to slide and drag easily while turning in the field.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mower • Small Tractor

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	170
Overall Diameter (mm)	408
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

Load capacity (Kg)

km/h / bar	4.90
15	480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 00:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..