

MULTIMAX MP 515 - Technical Specifications



Description

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Universal Vehicle • Fertilizer Truck

Version	STANDARD
Type	TL
Tyre Size	445/65 R 22.5 MPT
LI/SS	160 G

Dimensions International Standard

Section Width (mm)	444
Overall Diameter (mm)	1150
Static Loaded Radius (mm)	527
Rolling Circumference (mm)	3532
Rim Rec	13
Rim Alt	14
ECE	E11-54R-0017868

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0	4.5	6.0
90	1740	2060	2410	2750	3075	3390	3800	4500
65	1890	2235	2615	2985	3340	3675	4000	4885
40	2005	2365	2770	3165	3540	3900	4240	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..