

POWERTRAILER SR 331 - Technical Specifications



Description

POWERTRAILER SR 331 is BKT's brand-new All Steel radial tire specifically designed for trailers and tankers in transport applications. Engineered for both field and road usage, POWERTRAILER SR 331 distinguishes itself with good flotation properties in the fields as well as excellent traction on asphalt or other hard, improved surfaces. The All Steel construction stands for high load capacity, extraordinary casing stability, and an extended tire life. The special sidewall rib provides exceptional protection against impacts and the effects of tire rubbing, while the hexagonal bead with chafer reinforcement makes sure that the tire perfectly fits on the rim. In addition, the multi-block tread pattern ensures reduced rolling resistance, a uniform contact pressure, and smooth roadability. Thanks to all these features, POWERTRAILER SR 331 is synonym for fuel economy and road comfort.

UM

US Standard

Construction



Machinery

Agriculture: Tanker • Trailer

Version	IMPLEMENT
Туре	TL
Tyre Size	560/60 R 22.5
11/55	169 D

Dimensions US Standard

Usa code	94075997
Overall Width (inch)	21.9
Overall Diameter (inch)	49
Static Loaded Radius (inch)	22.2
Rolling Circumference (inch)	148.6
Rim Rec	AG 16.00
Rim Alt	17.00 ; AG18.00
ECE	E11-106R-0010147

Load capacity (lbs)

mph/psi	46	52	58	65	73	80	87
5	14960	16340	17960	19100	20250	21640	23020
15	13130	14340	15760	16770	17780	18990	20210
25	11300	12350	13570	14430	15300	16350	17390
30	10050	10990	12070	12840	13610	14540	15480
40	8310	9080	9970	10610	11250	12020	12800
43	7560	8260	9070	9660	10240	10930	11640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/02/2025 05:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..