

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	500/45 R 22.5
LI/SS	146 D/143 E

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1022
Static Loaded Radius (mm)	455
Rolling Circumference (mm)	3114
SRI (mm)	500
Rim Rec	AG 16.00
ECE	E4-106R-000786

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1000	1120	1390	1585	1830	2075	2265	2480	2725
65	1095	1230	1530	1740	2010	2280	2490	2730	3000
50	1330	1490	1855	2110	2435	2760	3015	3305	3630
40	1495	1675	2085	2370	2735	3105	3390	3715	4080
25	1735	1945	2420	2750	3180	3605	3935	4315	4740
10	1975	2215	2755	3135	3620	4105	4485	4915	5400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 00:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..