

## ROCK GRIP IND4 (RS) - Technical Specifications



### Description

ROCK GRIP PORT INDUSTRIAL IND-4 (RS) is a bias-ply tire designed for Reachstacker in several applications including industrial handling and steelworks. The special ROCK GRIP compound ensure particular heat resistance along with great stability and durability.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Reach Stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

## Dimensions US Standard

Usa code	94038527
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	74.3
Static Loaded Radius (inch)	34.2
Rolling Circumference (inch)	219.9
Rim Rec	13.00/2.5
TRA Code	IND4

## Load capacity (lbs)

mph / psi	145
5	59500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/02/2025 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..