



SKID POWER HD (A) - Data Sheet

Description

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Skid Steer



SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.5 - 8	STANDARD	97 A2	8	7.00 I - 55 ; I - 70 ; I - 90		210	460	207	1357	TL	E11-106R-005559
23 X 8.5 - 12	IMPLEMENT	87 A8	6	7.00 I - 55	7.00 I - 70 ; 7 JA	215	585	271	1764	TL	E11-106R-003361
23 X 8.50 - 12	IMPLEMENT	98 A8	12	7.00 I - 55	7.00 I - 70 ; 7 JA	215	585	271	1764	TL	E11-106R-003537
23 X 8.50 - 12	STANDARD		6	7.00 I - 55	7.00 I - 70 ; 7 JA	215	585	271	1764	TL	
23 X 8.50 - 12	STANDARD		12	7.00 I - 55	7.00 I - 70 ; 7 JA	215	585	271	1764	TL	E11-106R-003569
23 X 8.50 - 12	STANDARD		8	7.00 I - 55	7.00 I - 70 ; 7 JA	215	585	271	1764	TL	
26 X 12 - 12	IMPLEMENT	114 A8	12	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	305	660	297	1947	TL	E11-106R-003538
26 X 12 - 12	STANDARD		12	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	305	660	307	1989	TL	
26 X 12 - 12	STANDARD		10	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	305	660	297	1947	TL	
26 X 12 - 12	STANDARD		8	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	305	660	297	1947	TL	E11-106R-004118
27 X 10 - 12 (250/75 - 12)	INDUSTRIAL	152 A2	14	8.00 G		255	700	0	0	TT	E11-106R-006176
27 X 10.5 - 15	IMPLEMENT	105 A8	8	8 LB		256	684	326	2037	TL	E11-106R-003539
27 X 10.5 - 15	STANDARD		8	8 LB		256	684	326	2037	TL	E11-106R-007197
27 X 10.5 - 15	TRACTOR TRAILER	108 A6	8	8 LB		256	684	326	2037	TL	E11-106R-003376
27 X 8.5 - 15	IMPLEMENT	102 A8	8	7 JA		218	676	324	2004	TL	E11-106R-003540
27 X 8.50 - 15	STANDARD		8	7 JA		218	676	324	2004	TL	
31 X 15.5 - 15	IMPLEMENT	125 A8	10	13 LB		405	790	378	2411	TL	E11-106R-003375
31 X 15.5 - 15	STANDARD		8	13 LB		405	790	378	2411	TL	
31 X 15.5 - 15	STANDARD	139 A2/121 B	10	13 LB		405	790	378	2411	TL	E11-106R-003571
385/50 - 15	STANDARD		8	13 LB		375	770	365	2240	TL	
10 - 16.5	IMPLEMENT	116 A8	8	8.25		267	780	362	2350	TL	E11-106R-003665
10 - 16.5	STANDARD		10	8.25		267	780	362	2350	TL	E11-106R-005556
10 - 16.5	STANDARD		8	8.25		267	780	362	2350	TL	
12 - 16.5	IMPLEMENT	130 A8	12	9.75		324	850	388	2571	TL	E11-106R-003568
12 - 16.5	IMPLEMENT	125 A8	10	9.75		324	850	388	2571	TL	E11-106R-003541

12 - 16.5	STANDARD		14	9.75		324	850	388	2571	TL	
12 - 16.5	STANDARD		12	9.75		324	850	388	2571	TL	
12 - 16.5	STANDARD		10	9.75		324	850	388	2571	TL	
260/70 - 16.5 (10 - 16.5)	IMPLEMENT	120 A8	10	8.25		267	775	355	2295	TL	E4-106R-002338
31.5 X 13 - 16.5	IMPLEMENT	124 A8	10	9.75		330	795	363	2345	TL	E11-106R-003542
31.5 X 13 - 16.5	STANDARD		10	9.75		330	795	363	2345	TL	
33 X 15.5 - 16.5	IMPLEMENT	131 A8	12	13.00		394	838	387	2563	TL	E11-106R-003018
33 X 15.5 - 16.5	STANDARD	151 A2	14	13.00		394	838	387	2563	TL	E11-106R-006606
33 X 15.5 - 16.5	STANDARD	148 A2	12	13.00		394	838	387	2563	TL	E11-106R-003505
14 - 17.5	IMPLEMENT	140 A8	14	10.50		350	930	420	2744	TL	
14 - 17.5	STANDARD		14	10.50		350	930	420	2744	TL	
15 - 19.5	IMPLEMENT	146 A8	14	11.75	12.25	400	1019	463	3075	TL	E11-106R-003656
15 - 19.5	STANDARD		14	11.75	12.25	400	1019	463	3075	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 16:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..