

SKID POWER - Technical Specifications



Description

SKID POWER has been designed for skid steers in construction applications. It shows excellent traction as well as enhanced self-cleaning features. The tire features an extra deep tread along with extra sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER is the ideal tire for loose surfaces.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer

Version	IMPLEMENT
Type	TL
Tyre Size	23 X 10.5 - 12
LI/SS DRIVE WHEEL	90 A8
LI/SS FREE ROLLING	90 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	264
Overall Diameter (mm)	590
Rim Rec	8.5 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-008809

Load capacity (Kg)

km/h / bar	2.80
40 FR	600
40 DW	600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/02/2025 05:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..