

SUPER GRADER - Technical Specifications



Description

SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Grader

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	340
Overall Diameter (mm)	1275
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3800
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2
Tread Depth	25

Load capacity (Kg)

km/h / bar	3.00
40	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/02/2025 05:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..