

TR 387 IND - Technical Specifications



Description

TR 387 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Compactor • Industrial Tractor • Trailer

Version	DUAL BEAD
Type	TL
Tyre Size	620/75 - 30 (23.1 - 30)
LI/SS	161 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	605
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	770
Rolling Circumference (mm)	4909
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R3

Load capacity (Kg)

km/h / bar	2.30
30	4625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 15:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..