

TR 387 IND - Data Sheet



Description

TR 387 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Compactor • Industrial Tractor • Trailer

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
620/75 - 30 (23.1 - 30)	DUAL BEAD	R3	161 A6	16	DW 20 A ; DW 20 B		605	1675	770	4909	TL
620/75 - 30 (23.1 - 30)	DUAL BEAD HD	R3	164 A6	18	DW 20 A ; DW 20 B		605	1675			TL
24.5 - 32	DUAL BEAD HD	R3	164 A6	16	DH 21	DH 21 B ; DH 21 H ; DH 21 HB	625	1755	790	5226	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 15:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..