

# TR 678 IND - Technical Specifications



## Description

TR 678 IND has been specially designed for industrial applications. Its robust lug design provides excellent traction and self-cleaning. The strong casing structure stands for high load capacity whereas its steel belts protect the tire from punctures and damages. TR 678 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains under extreme conditions.

## UM

US Standard

## Construction

 BIAS

## Machinery

Industrial: Excavator • Trailer

<b>Version</b>	DUAL BEAD
<b>Type</b>	TL
<b>Tyre Size</b>	600/40 - 22.5
<b>LI/SS DRIVE WHEEL</b>	157 A8
<b>LI/SS FREE ROLLING</b>	169 A8

## Dimensions US Standard

Usa code	94065301
Section Width (inch)	24.2
Overall Diameter (inch)	42.7
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	128.5
Rim Rec	AG 20.00
ECE	E11-106R-006973

## Load capacity (lbs)

mph / psi	60
25 FR	12790
25 DW	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/02/2025 05:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..