

VIJETA - Data Sheet



Description

VIJETA is an agricultural tire suitable for both on- and offthe-road applications. The 5-rib pattern optimizes load distribution. In addition, the wear-resistant compound and the strong casing stand for a long tire life-cycle.

UM

International Standard

Construction



Machinery

Agriculture: Trailer

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Туре	ECE
5.00 - 19	STANDARD	94 A3	6	3.00		140	755	TT	
6.00 - 19	STANDARD	105 A3	8	4.00		175	810	TT	
7.00 - 19	STANDARD		10	5.00		195	852	TT	E11-106R-004106
8.00 - 19	STANDARD		10	5.00		225	912	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/02/2025 23:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..